

➤ **Double-sided adhesive pure acrylate tape**

very strong/very strong adhesive

SPRINTIS Schenk GmbH & Co. KG
Ludwig-Weis-Str. 11 · D-97082 Würzburg
Tel. +49 (0) 931 / 40 41 6-240 · Fax: -100

www.sprintis.de · info@sprintis.de

02/2021

Applications & purposes

Well suited for PVC, acrylic, glass/ceramics.
Mounting of signs, fascias, scales, fixing of displays and advertising material.

Characteristics

Adhesive type	Pure acrylate
Carrier material	Without
Carrier colour	Transparent
Thickness (adhesive & carrier)	2 mm
Peel adhesion, adhesive strength (open side)	35 ± 2 N / 25 mm (FTM 1)
Shear adhesion	> 183 h (FTM 8)
Release liner material	PE foil
Release liner colour	red
Temperature from/to	-20 °C to +100 °C
Food contact	Indirect (Level 2)

Storage recommendation / Shelf life

Under normal storage conditions in a room climate (approx. 50% relative humidity & approx. 20 °C room temperature) the product in its original packaging has a storage period of at least 12 months after receipt by the customer.

Disclaimer:

Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third part. We cannot assume any liability for the use of our products in conjunction with other materials.