Fabric tape, TK30



SPRINTIS Schenk GmbH & Co. KG Ludwig-Weis-Str. 11 · D-97082 Würzburg Tel. +49(0) 931 / 40 41 6-288 www.sprintis.eu · info@sprintis.eu

Version 12/2022

Applications & purposes:

The matt fabric tape with its light-absorbing, non-reflective plastic coating is suitable for fastening, marking, masking or repairing in industry, commerce or in the DIY and housework sector. On-stage and back-stage, it can be used to cover shiny backgrounds or apply temporary floor markings in the field of event and stage technology, for example in theatres, opera houses and cinemas

Characteristics

Adhesive type	nature rubber
Carrier material	PE extruded fabric
Thickness (adhesive & carrier)	0,30 mm
Peel adhesion, adhesive strength	9N/25mm
tensile strength	95n/25mm
Temperature from/to	-35° to +80°
Food contact	not tested

Storage recommendation / Shelf life

Under normal storage conditions in a room climate (approx. 50% relative humidity & approx. $20\,^{\circ}$ C room temperature) the product in its original packaging has a storage period of at least 12 months after receipt by the customer.

Disclaimer:

Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third part. We cannot assume any liability for the use of our products in conjunction with other materials.